



CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

PHS102DS Smoke detector

PHS102DS-2-LED Smoke detector with output for LED PHS102DS-4-12 Smoke detector with 12V relay PHS102DS-4-24 Smoke detector with 24V relay

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

PH Svesis S.A.

Vrises - 69th km National Road

Athens, Lamia 34100, Greece

and produced in the manufacturing plant:

CPA10001

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-7:2000/A1:2002/A2:2006 : Fire detection and fire alarm systems - Part 7: Smoke detectors - Point detectors

using scattered light, transmitted light or ionization

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2020-10-23.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate issued 2020-01-20)

This certificate was first issued 2020-01-20.

Merete Poulsen Responsible for evaluation Thomas Wilson
Responsible for certification decision







Annex 1

EXTENT

Type:

PHS102DS Smoke detector

PHS102DS-2-LED Smoke detector with output for LED PHS102DS-4-12 Smoke detector with 12V relay PHS102DS-4-24 Smoke detector with 24V relay

Bases:

P/N 772912 2 wire base for detectors

P/N 774912 4 wire base for detectors

P/N 882912 2 wire base for detectors (high version) P/N 884912 4 wire base for detectors (high version)

Performance

Essential characteristics	Clauses in EN 54-7:2000	Performance		
Nominal activation	4.8, 5.2, 5.3, 5.4, 5.6, 5.7, 5.18	Pass		
conditions/Sensitivity, Response				
delay (response time) and				
Performance under fire conditions				
Operational reliability	4.2 to 4.7, 4.9 to 4.11	Pass		
Tolerance to supply voltage	5.5	Pass		
Durability of operational reliability	5.8, 5.9	Pass		
and response delay; temperature				
resistance				
Durability of operational reliability;	5.13 to 5.16	Pass		
vibration resistance				
Durability of operational reliability;	5.10, 5.11	Pass		
humidity resistance				
Durability of operational reliability;	5.12	Pass		
corrosion resistance				
Durability of operational reliability;	5.17	Pass		
electrical stability				







Annex 2

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
DELTA	DANAK-199728	2004-06-04
Danish Electronics, Light & acoustics Venlighedsvej 4 2970 Hørsholm Denmark	Project no.: E810164-2	
DELTA	Statement concerning alternative base for detectors	2004-09-03







Annex 3

TECHNICAL BASIS

File Number	Title	Date
Documentation summarization	NB 338 Smoke/Heat detector, 10-0009-r01_NB338	2014-06-27

