



EXIDUS
Indoor Emergency Lighting

CE Certificate Number
00115/101/1/2017

ENEC Approved

EXIDUS

Indoor Emergency Lighting

General Specifications

- Indoor EXIT sign for ceiling or wall mounting.
- Control and programming button.
- 3 x status LEDs and reset button.
- Built-in self-test feature.
- Easy identification of Faults (battery, lighting elements).
- Slim design.
- Fast and easy installation.
- Five (5) luminance levels for each operating mode.
- This EXIT sign comes in 2 variations for areas up to 20 meters (exidus 1) of visibility or up to 30 meters (exidus 2) of visibility.
- ENEC approved. Certified to EN60598.
- The EXIDUS emergency lighting can be provided with left, right or down pointing arrows.



Technical Specifications

Power Supply	230VAC / 50Hz
Max. Power Consumption	Less than 5VA
Light Source	12 LED
Battery	3.6V 1.0Ah NiCd
Emergency Operation Time	From 150min to 240min depending on luminance setting
Luminance setting	5 steps (20, 40, 60, 80 & 100%)
Light source intensity (230V)	100lm
Mounting	Wall / ceiling
Switch over Voltage	Between 150 ~ 190V
IP rating	IP20
Isolation Category	Double isolation
Environmental	Temperature: +5 to 45 °C Humidity: 5 to 95% RH, non condensating
Indication Area Dimensions [WxHxD]	314x150x6 mm (exidus1), 314x100x6 mm (exidus2)
Dimensions [WxHxD]	Main body: 320x64x27mm
Guarantee	3 years (1 year for the battery)

