



SIR/V & SIR/VS

Outdoor, Tampering Protected &
Battery Back-up Sirens

SIR/PLL & SIR/PLSL

Outdoor, Tampering Protected & Battery Back-up Sirens



The SIR/V and SIR/VS sirens are designed and manufactured to contain both maximum function abilities and security.

The housing aesthetically pleasant, with built in FLASH and large exterior room for the company "logo" is made of POLYCARBONATE plastic. Interior metal cover made of galvanized steel sheets. The robust design and excellent material ensure maximum protection endurance to all weather conditions.

SIR/V is certified to EN50131-4 Standard, Security Grade 3, Environmental Class IV.

General Specifications

- Complete initial connection can be made before panel power up. It's put in STANDBY mode only when the + or -SSP command is given.
- The siren is activated when the alarm panel's voltage drops below 9.5 VDC.
- High Bright LED Flash.
- Protection of the siren from short circuit in the Flash.
- Protection switch TAMPER from opening the cover or removing the siren from the wall.
- Maximum alarm duration when the SSP is off.
- UV protected, self extinguishing Polycarbonate plastic box.
- Available in white and silver color.
- Flash in red and orange color.

Technical Specifications

Operating Voltage:	11-14 VDC
Standby Current Drain:	12mA ±5%
Alarm Current Drain:	1.6A ±5%
Supported Battery Type:	12V 2.3Ah / 12V 7Ah
Acoustic Pressure:	110dB±5%@1m (SIR/V) 105dB±5%@1m (SIR/VS)
Type of acoustic output:	Acoustic output is modulated tone
Operating Frequency (Audio):	1600 - 2400 Hz
Alarm Duration (Factory setting):	1. From 4 to 5 min 2. From 5 to 6 min 3. From 8 to 10 min
Max. Tamper Switch Ratings:	1A / 30V
Visual Alarm Indicator:	High Bright LED
SSP Voltage:	± 12V
IP Rating (Ingress Protection Rating):	IPX4
IK Rating (Impact Protection Rating):	IK08
Dimensions (HxWxD) [mm]:	275x250x90
Weight:	2.52Kgr. (SIR/V) 2.4Kgr. (SIR/VS)