



EXIDUS
Indoor Emergency Lighting

EXIDUS

Indoor Emergency Lighting

General Specifications

- Indoor EXIT sign for ceiling or wall mounting.
- Control and programming button.
- 3 x status LEDs and reset button.
- Built-in self-test feature.
- Easy identification of Faults (battery, lighting elements).
- Slim design.
- Fast and easy installation.
- Five (5) luminance levels for each operating mode.
- This EXIT sign comes in 2 variations for areas up to 20 meters (Exidus 1) of visibility or up to 30 meters (exidus 2) of visibility.
- ENEC approved.
- The EXIDUS emergency lighting can be provided with left, right or down pointing arrows.



Technical Specifications

Power Supply:	230VAC / 50Hz
Max. Power Consumption:	Less than 5VA
Light Source:	12 LED
Battery:	3.6V 1.0Ah NiCd
Emergency Operation Time:	From 150min to 240min depending on luminance setting
Luminance setting:	5 steps (20, 40, 60, 80 & 100%)
Light source intensity (230V):	100lm
Mounting:	Wall / ceiling
Switch over Voltage:	Between 150 ~ 190V
IP rating:	IP20
Isolation Category:	Double isolation
Environmental:	Temperature: +5 to 45 °C Humidity: 5 to 95% RH, non condensating
Indication Area Dimensions [WxHxD]:	Exidus 1: 314x90x6 mm Exidus 2: 314x140x6 mm
Dimensions [WxHxD] (no brackets):	Exidus 1: 320x215x27 mm, Exidus 2: 320x220x27 mm
Guarantee:	3 years (1 year for the battery)

